



Self-contained TCP/IP network ready color camera with C / CS mount 4mm manual iris lens, 10 / 100 base T ethernet port, using MPEG-4 compression for high quality and fast frame rate.

CPU		Trimedia PNX1300
RAM		16MB SDRAM
ROM		2MB Flash ROM
Image sensor		1/3" CCD color (290,000 pixels)
Illumination		1.0 Lux @ F 1.2
camera functions		AGC, AWB, AES
Shutter speeds		1/60 (PAL 1/50) ~ 1/15000 SEC
Video Algorithm		MPEG4 (Short header mode) JPEG for still frame
Resolution		420 Lines
Video resolution NTSC		30fps 176 x 120, 30fps 325 x 240
Video resolution PAL		25fps 176 x 144 30fps 352 x 288
Picture elements		NTSC: 512 x 492 PAL:512 x 582
Audio		Options: 24kbps, 8kbps
Mic		Omni directional, 50-15KHz, S/N >60dB
Serial port		9p D-SUB, RS232 0r RS485(PTZ cam ctrl. or modem)max 115.2kbps
Network protocol		TCP/IP, HTTP, SMTP, FTP, Telnet, NTP, DNS, DHCP
Ethernet		10 TbaseT, 100baseT, Fast ethernet auto negotiation

Modem		PPP (dial-up, direct cable connection)
Input / Outputs		1 x sensor I/) max 12V DC 50ma, relay O/ P 24V DC 1A / 125V AC 0.5A
Viewing requirements		OS: MS wincows 98, SE, ME,NT4, 2000, XP
Browser		IE V.5.0 and above
LED indicators, Heartbeat, Status		
Dimensions		143 x 93.8 x 71.6 mm
Weight		700g
Power		12V DC @ 1.5A
EMI/Safety		CE, FCC, BSMI
Operating environment		0C ~ +50C R H. 95%
Software details		Remote configuration and control for 4 de- vices
~		Event triggered, scheduled, manual recording
~		Instant search with preview windows
~		Fas/Slow forward replay and pause
~		Hard disk quota warning
~		Scheduled back-up
~		AVI format export
~		16 channel commercial version at extra cost

\$399

CctvIP

For More Information

**42 BOTANY RD ALEXANDRIA
NSW 2015, SYDNEY AUSTRALIA
PHONE: 1300 130 508 FAX: 02 9698 5476
www.australsurveillance.com.au
sales@australsurveillance.com.au
ABN 85 388 051 001
MASTER SECURITY LICENCE No. 408916063**