



ZoomCamCol

Colour 270x Zoom Camera

High Resolution Panasonic Colour camera with integrated Canon Zoom lens

Specifications:

- Video System: PAL Colour fully compatible with Australian TV System.
- Image Device: 795 (H) x 596 (V) 473 820 Pixel 1/4" LOW BLEMISH PANASONIC Image Sensor.
- Day night capable (switched to low light BW in low light conditions)
- Video Output (1): 1 v p-p Composite Video 75 ohms, suit Australian TV, VCR, AV & Video inputs, BNC socket. Video Output (2): S-Video (Y/C), Luminance 1 v p-p 75 ohms, Chrominance 0.3 v p-p Burst 75 ohms, 4 pin Mini-DIN socket.
- Lens: CANON Motorised Focus/Zoom/Iris, 22X Optical ZOOM, F1.6 ~ F3.8, focal length 4 mm ~ 88 mm, Automatic Iris, Automatic / Manual Focus, 64 Zoom/Focus Positions.
 - Digital Zoom: 10 x, total 220x zoom capability
- Horizontal Resolution: 600 + lines. Better than Super-VHS resolution.
 - Minimum Illumination: 1.5 lux @ F1.2 (5600° Kelvin),
- Automatic Electronic Shutter (AES): 1/50 to 1/100 000 second, 20 milliseconds to 10 microseconds.

SPECIFICATIONS (Continued)

- Automatic Gain Control (AGC): 18 dB Max.
- Signal to Noise ratio: Typically 52 dB, minimum 48 dB, measured with AGC off.
 - Backlight Compensation (BLC): 48 Zones.
 - White Balance: ATW / AWB / FIX.
 - White Balance Range: ATW 3200° ~ 9 600° Kelvin. AWB/FIX 3200° Kelvin.
 - Negative Image: On / Off via OSD.
- Power Requirements: 12 Volts DC Regulated, 500 milliamps, via cable provided
 - Can be remotely operated via RS485 or 5 x rear mounted switches
 - Dimensions: 59 mm Wide, 80 mm High, 120 mm Deep, 450 grams.

Made by Taiwan's largest Camera maker in an ISO 9001 &
ISO-14001 certified factory.

\$599

(CctvZOOM)

Options

RS485 to USB Convertor.....\$265

Outdoor Housing to suite with Bracket.....\$99

FOR MORE INFORMATION

42 Botany Rd Alexandria NSW 2015

PHONE: 1300 130 508 FAX: (02) 9698 5476

www.australsurveillance.com.au

ABN 85 388 051 001

MASTER SECURITY LICENCE No. 408916063