

GSM Bug Instructions

1. To remove back cover copy as shown in image:



Press this button and cover should slip out.
You may need to press it with your thumb
and get your nail under the edge to pull it off.

2. Remove battery as shown:



The two clips either side of the SIM
section have arrows pointing
outwards, push them both out and
the battery will pop up.

3. Insert SIM card:



Place the SIM card so the gold parts
are touching. Any active SIM card
will work providing it's not 3G.

4. Put the battery back in with the gold parts touching. You'll know it's the right way when it slips in. Replace cover by putting the bottom hooks either side of the SIM card so the cover sits nicely on top then lock into place.
5. Switch the phone on by pressing the left side of the button on the top of the device and holding for 3-5 seconds until the screen lights up.
6. Give the phone about a minute to start up then press the button below Menu on the screen.



Menu button

7. It will now list the options available in the phone, to go next, press the up button and the Profiles option will come up.
8. Select the Silent profile then return to the main screen and lock the keypad (press Menu then *).



9. Press and hold the star button for 2 seconds then press 0 (you may need to try a few times to get the timing right).
10. When the screen goes black it's in spy mode. To listen in, dial the number of the SIM card from any other phone and you can hear up to 7m within the area of the spy phone.
11. To return to normal mode, press star for 2 seconds then 0, unlock keypad, go to Profiles option and select General.